



Guying kit for elevation mast

Reference: KITHAU

Maintenance and consolidation of lightning conductor elevation masts shrouds 3 points.

Stainless steel kit for 3-point guying.

Maintaining up to 4 items of extendable poles of 2.00 meters in height. The admissible height is 6.50 meters.

Compatibility for installations with lightning rod early streamer emission, air terminal, and single lightning rod tip.



Technical specifications

| | |
|------------------------|---|
| Composition of the kit | Twisted stainless steel cables Ø 2mm (50 meters) Stainless steel cable clamps (x 18) Turnbuckles (x 3) Heart terminals (x 6) Cable / mast fixing (x 1) |
| Material | Stainless steel |
| Supply included | Supplied assembled with stainless steel screws |
| Typical applications | Guying kit for lightning rod support masts, Support and consolidation of up to 4 elements of extendable masts 2.00 meters high, 3-point mechanical fixings, Allowable height 6.50 meters. |
| Adaptable products | MAT-IE range, TRPG01, TRPG02... |
| Standard packaging | Bag of 1 complete kit |
| Unit weight | 2.550 kg |
| Material to standards | EN NF 62305, EN NF 62561-4, NF C 17102 |
| Reference | KITHAU |



RESEARCH AND DEVELOPEMENT



MANUFACTURE



TECHNICAL AND COMMERCIAL



SALE EXPORT



INSTALLATION



MAINTENANCE